

FEATURES :

- 7PIN SIP Package
- No-load input current as low as 5mA
- Continuous short-circuit protection
- High Efficiency up to 89%
- Unregulated Output Types
- 1.5KVDC ~ 6KVDC Isolation
- Operating Temperature:-40°C TO +105°C
- Industry Standard Pinout
- Design refer to IEC62368, UL62368, EN62368

Specifications typical at TA=25°C, nominal input voltage and rated output current unless otherwise specified

Part Number	Output Voltage	Output Current	Efficiency	Capacitive Load(μF)
	Vdc	mA	%TYP	Max.
12DC-05S05NP2(H3)	5	400	84	2400
12DC-05S09NP2(H3)	9	223	85	820
12DC-05S12NP2(H3)	12	167	85	470
12DC-05S15NP2(H3)	15	133	86	220
12DC-05S24NP2(H3)	24	84	87	100
12DC-05D05NP2(H3)	±5	±200	82	±1200
12DC-05D09NP2(H3)	±9	±112	85	±330
12DC-05D12NP2(H3)	±12	±84	85	±330
12DC-05D15NP2(H3)	±15	±67	87	±100
12DC-05D24NP2(H3)	±24	±42	88	±47
12DC-XXS05NP2(H3)	5	400	85	2400
12DC-XXS09NP2(H3)	9	223	87	820
12DC-XXS12NP2(H3)	12	167	87	470
12DC-XXS15NP2(H3)	15	133	88	220
12DC-XXS24NP2(H3)	24	84	89	100
12DC-XXD05NP2(H3)	±5	±200	82	±1200
12DC-XXD09NP2(H3)	±9	±112	85	±330
12DC-XXD12NP2(H3)	±12	±84	87	±330
12DC-XXD15NP2(H3)	±15	±67	88	±100
12DC-XXD24NP2(H3)	±24	±42	89	±47

Note:


1:No suffix is standard isolation (1.5KVDC) e.g, 12DC-05S05NP2 ,
 *add suffix "H3" for 3KVDC isolation, *add suffix "H4" for 4KVDC isolation,
 *add suffix "H5" for 5.2KVDC isolation, *add suffix "H6" for 6KVDC isolation,
 2:"XX" Is Input Voltage : 12=12Vdc,15=15Vdc, 24=24Vdc
 e.g, 12DC-12S05NP2, 12DC-15S12NP2H3, 12DC-24S15N2PH6

YUAN DEAN SCIENTIFIC




DC-DC Converter
12DC-2W SERIES

2Watt
 1.5~6KV Isolated
 Single & Dual Output
 SIP7



Temperature Derating Graph



www.yds.com.tw



TEL : 886-6-3842899

FAX : 886-6-3843288

E-MAIL: ydsweb@yds.com.tw

Rev: 1 2021/10/07

Input Specifications

Parameters	Conditions	Min	Typ	Max	Units
Voltage Range	Vo,lo Nom		±10		%
Filter	Capacitor				

Output Specifications

Parameters	Conditions	Min	Typ	Max	Units
Voltage Tolerance	100% full load			±5	%
Short Circuit Protection	Continuous				
Line Regulation	For 1.0% OF Vin		1.2		%
Load Regulation	5V (10% To 100% F.L)		8	15	%
	9V (10% To 100% F.L)		6	10	%
	12V (10% To 100% F.L)		5	10	%
	15V (10% To 100% F.L)		4	10	%
	24V (10% To 100% F.L)		3	10	%
Ripple & Noise	BW=DC To 20MHz		75	150	mVp-p

General Specifications


Parameters	Conditions	Min	Typ	Max	Units
Isolation Resistance	500Vdc	1000			MΩ
Isolation Capacitance	Input-output, 100KHz/0.1V		20		pF
Switching Frequency	Full load,nominal input @5V Vin		215		KHz
	Full load,nominal input @other Vin		250		KHz
Operation Temperature		-40		+105	°C
Storage Temperature		-55		+125	°C
Humidity	Non Condensing			95	%
Cooling	Free air Convection				
Case material	DAP				
MTBF	MIL-HDBK-217F@25°C	3500000			Hours
Weight			2.1		g
Dimensions		19.5x6.0x10.0			mm

Part Number

12DC - 15 S 05 N P 2 H3
 A B C D E F G H

A:Series
 B:Input Voltage
 C:Single(S)/Dual(D)Output
 D:Output Voltage
 E:Unregulated(N)
 F:Protection
 G:Output Power
 H:Isolation Voltage


Tolerance Envelope Graph



Electromagnetic Compatibility (EMC)

EMI	CE	CISPR32/EN55032 CLASS B (see Fig. 1 for recommended circuit)
	RE	CISPR32/EN55032 CLASS B (see Fig. 1 for recommended circuit)
EMS	ESD	IEC/EN61000-4-2 Air ±8kV , Contact ±4kV perf. Criteria B


Packaging



Size(mm)			
A	B	C	D
9.5	16.5	522	5.0



Recommended Test Circuit



EMC (CLASS B) compliance circuit





Fig.1

EMC recommended circuit value table

EMC recommended circuit value table		
EMI	C1	4.7μF /50V
	C2	4.7μF /50V
	CY	1nF/4kV
	C3	Recommended Test Circuit
	L	6.8μH

Markings and Dimensions



UNIT:mm Unless otherwise specified,all tolerances are ±0.25

PIN Connection

PIN	1	2	5	6	7
Single	+Vin	-Vin	-Vout	No Pin	+Vout
Dual	+Vin	-Vin	-Vout	Com	+Vout